



BENELLI DEFENSE



IBDT

4

m4

18,5" TELESCOPIC STOCK
14" + DOOR-BREACHER TELESCOPIC STOCK

8

m4
BATTLE BROWN

18,5" TELESCOPIC STOCK
14"+ DOOR-BREACHER TELESCOPIC STOCK

12

m3

18,5" TELESCOPIC STOCK
14" + DOOR-BREACHER TELESCOPIC STOCK

16

m3
GRIP HANDLE

14" + DOOR-BREACHER GRIP HANDLE

18

m2

18,5" PISTOL GRIP STOCK
14"+ DOOR-BREACHER PISTOL GRIP STOCK

22

nova

18,5" MONOBLOCK STOCK/RECEIVER
14"+ DOOR-BREACHER MONOBLOCK STOCK/RECEIVER

26

supernova

18,5" TELESCOPIC STOCK
14"+DOOR-BREACHER TELESCOPIC STOCK

30

supernova
GRIP HANDLE

14" + DOOR-BREACHER GRIP HANDLE

32

MR1

12,5"+2" TELESCOPIC STOCK

36

optionals

 **Benelli**

The M4 is the semiautomatic shotgun

with Benelli patent self-cleaning auto-regulating gas system with rotating locking head. The high-tech nature of its design and development is thanks to Benelli's experience in the design of semiautomatic shotguns.

18,5" TELESCOPIC STOCK



14"+ DOOR-BREACHER TELESCOPIC STOCK





A.R.G.O. system

The M4 has an ingenious, cutting-edge, gas operated mechanical system, patented by Benelli and known as Auto Regulating Gas Operating (A.R.G.O.).

The M4 was selected by the US armed forces

as its Joint Service Combat Shotgun, after passing all of the stringent acceptance tests for efficiency, reliability, ballistic precision and strength in the worst possible conditions. The M4 is also available with telescopic stock that can be adjusted in 5 positions.

	M4 BLACK 18,5" TELESCOPIC STOCK	M4 BLACK 14"+ DOOR-BREACHER TELESCOPIC STOCK
OPERATION Semiautomatic Auto Regulating Gas Operating		
GAUGE	12	12
CHAMBER	3" MAGNUM	3" MAGNUM
SAFETY ordinary (mechanic and manually operated on trigger) and automatic (against premature firing on disconnecter); over-sized, reversible (right- /left-handed) safety button		
CUT-OFF lever for rapid cartridge replacement and red cocked hammer indicator		
TRIGGER LOAD between 2.500 and 3.250 kg - 30 and 36 N		
BARREL LENGTH (mm)	470	355
MAGAZINE CAPACITY 6 Magnum or 7 standard cartridges (+1 in chamber)		

	M4 BLACK 18,5" TELESCOPIC STOCK	M4 BLACK 14"+ DOOR-BREACHER TELESCOPIC STOCK
MAGAZINE CAPACITY 3 Magnum or 4 standard cartridges (+1 in chamber)		
STOCK DISTANCE FROM TRIGGER (mm)	360 extended 239 retracted	360 extended 239 retracted
SIGHTS Ghost Ring rear sight with diopter with adjustable windage and elevation and protective side lugs; fixed sight for Ghost Ring Sight; Picatinny Rail		
STOCK in tecnopolymer telescopic stock, collapsible to 121 mm		
WEIGHT g (unloaded weapon)	3780	3700
TOTAL LENGTH (mm)	1010 extended 889 retracted	895 extended 774 retracted
FINISH black anodised receiver; hammered barrel in Ni-Cr-Mo steel with chrome lining and phosphate-coated exterior		

Compact and multipurpose

The M4 model with short magazine tube (3 magnum or 4 standard cartridges + 1 in the chamber) and 14" (355 mm), barrel is a compact weapon that has been devised for use in more restricted environments.

18,5" TELESCOPIC STOCK



14"+ DOOR-BREACHER TELESCOPIC STOCK



CERAKOTE treatment

External Ceramic coating
(federal standard field grab) that confers the treated surfaces of the M4 exceptional resistance against extreme environmental conditions, erosion, corrosion and scratching.

Versatile and reliable

The versatility of the m4 shotgun can also be seen in its interchangeable stocks: telescopic, fixed stock or pistol grip stock, in technopolymer reinforced with fibre-glass, replaceable without tools. The choice of tubular magazine is fundamental since it allows the continual reloading of cartridges without having to loosen grip or move from a firing position: the weapon is thus always loaded and ready to fire and there are no breaks in defensive cover.

All models have a limited number of parts, which have been assembled in such a way as to allow quick and easy stripping and re-assembly without tools.

	M4 BATTLE BROWN 18,5” TELESCOPIC STOCK	M4 BATTLE BROWN 14”+ DOOR-BREACHER TELESCOPIC STOCK
OPERATION Semiautomatic Auto Regulating Gas Operating		
GAUGE	12	12
CHAMBER	3” MAGNUM	3” MAGNUM
SAFETY ordinary (mechanic and manually operated on trigger) and automatic (against premature firing on disconnecter); over-sized, reversible (right-/left-handed) safety button		
CUT-OFF lever for rapid cartridge replacement and red cocked hammer indicator		
TRIGGER LOAD between 2.500 and 3.250 kg - 30 and 36 N		
BARREL LENGTH (mm)	470	355
MAGAZINE CAPACITY 6 Magnum or 7 standard cartridges (+1 in chamber)		
MAGAZINE CAPACITY 3 Magnum or 4 standard cartridges (+1 in chamber)		
STOCK DISTANCE FROM TRIGGER (mm)	360 extended 239 retracted	360 extended 239 retracted

	M4 BATTLE BROWN 18,5” TELESCOPIC STOCK	M4 BATTLE BROWN 14”+ DOOR-BREACHER TELESCOPIC STOCK
SIGHTS Ghost Ring rear sight with diopter with adjustable windage and elevation and protective side lugs; fixed sight for Ghost Ring Sight; Picatinny Rail		
STOCK in tecnopolymer telescopic stock, collapsible to 121 mm		
WEIGHT g (unloaded weapon)	3780	3700
TOTAL LENGTH (mm)	1010 extended 889 retracted	895 extended 774 retracted
EXTERNAL CERAMIC COATING (federal standard field grab) that confers the treated surfaces of the M4 exceptional resistance against extreme environmental conditions, erosion, corrosion and scratching		

M3 is a dual mode (semiautomatic and pump action)

M3 is one of the best possible choice for any operational or defense requirement. This is thanks to its flexible use (lethal and less than lethal ammos), easy handling, precision and high firing volume.

18,5" TELESCOPIC STOCK



14"+ DOOR-BREACHER TELESCOPIC STOCK





Lever to switch from semiautomatic to pump action



Two different operating mechanisms have been brought together in a single shotgun:

semiautomatic and pump, to meet any defense requirement. The interchangeable stocks-fixed drop, variable drop and pistol grip-only increase the versatility of this weapon.

SLUG



00 BUCKSHOT



DOOR-BREACHING



LESS THAN LETHAL



OPERATION
Benelli Inertial System semiautomatic convertible to Pump Action

GAUGE

12

CHAMBER

3" MAGNUM

SAFETY ordinary (mechanic and manually operated on trigger) and automatic (against premature firing on disconnecter); over-sized, reversible (right-/left-handed) safety button

CUT-OFF lever for rapid cartridge replacement and red cocked hammer indicator

TRIGGER LOAD
between 2.500 and 3.250 kg - 30 and 36 N

BARREL LENGTH (mm)

470

MAGAZINE CAPACITY
6 Magnum or 7 standard cartridges (+1 in chamber)

MAGAZINE CAPACITY
3 Magnum or 4 standard cartridges (+1 in chamber)

M3 18,5" TELESCOPIC STOCK	M3 14" + DOOR-BREACHER TELESCOPIC STOCK
<div></div>	<div></div>
12	12
3" MAGNUM	3" MAGNUM
<div></div>	<div></div>
<div></div>	<div></div>
<div></div>	<div></div>
<div></div>	<div></div>
470	355
<div></div>	
	<div></div>

STOCK DISTANCE FROM TRIGGER (mm)

360 extended 239 retracted

360 extended 239 retracted

SIGHTS
Ghost Ring rear sight with diopter with adjustable windage and elevation and protective side lugs; fixed sight for Ghost Ring Sight; Picatinny Rail

STOCK in technopolymer telescopic stock, collapsible to 121 mm

WEIGHT g (unloaded weapon)

3470

3390

TOTAL LENGTH (mm)

1010 extended 889 retracted

895 extended 774 retracted

FINISH
black anodised receiver; hammered barrel in Ni-Cr-Mo steel with chrome lining and phosphate-coated exterior

M3 18,5" TELESCOPIC STOCK	M3 14" + DOOR-BREACHER TELESCOPIC STOCK
<div></div>	<div></div>
360 extended 239 retracted	360 extended 239 retracted
<div></div>	<div></div>
<div></div>	<div></div>
<div></div>	<div></div>
3470	3390
1010 extended 889 retracted	895 extended 774 retracted
<div></div>	<div></div>

Durable and precise

The receiver is in matt black, anodised, Ergal alluminium alloy, and the barrels are in Nickel-Chrome-Molybdenum steel with chrome-plated lining and matted blued exterior.

The stock and fore-end are in tecnopolymer with fibre-glass reinforcements and are inalterable as well as able to withstand humidity, shocks and abrasion.



	M3 14" + DOOR-BREACHER GRIP HANDLE		M3 14" + DOOR-BREACHER GRIP HANDLE
OPERATION Benelli Inertial System semiautomatic convertible to Pump Action	•	BARREL LENGTH 14" (355 mm)	•
GAUGE	12	MAGAZINE CAPACITY 3 Magnum or 4 standard cartridges (+1 in chamber)	•
CHAMBER	3" MAGNUM	STOCK DISTANCE FROM TRIGGER (mm)	360
SAFETY ordinary (mechanic and manually operated on trigger) and automatic (against premature firing on disconnecter); over-sized, reversible (right- /left-handed) safety button	•	GRIP HANDLE	•
CUT-OFF lever for rapid cartridge replacement and red cocked hammer indicator	•	WEIGHT g (unloaded weapon)	2800
TRIGGER LOAD between 2.500 and 3.250 kg - 30 and 36 N	•	TOTAL LENGTH (mm)	630
		FINISH black anodised receiver; hammered barrel in Ni-Cr-Mo steel with chrome lining and phosphate-coated exterior	•

14" + DOOR-BREACHER GRIP HANDLE



Years of experience

The M2 has been realized from Benelli Armi's Research and Development Centre, thanks to years of experience in the manufacturing of semiautomatic shotguns.

18,5" PISTOL GRIP STOCK



14"+ DOOR-BREACHER PISTOL GRIP STOCK





Inertia Driven System

The Inertia System mechanism, the rigorous design and essential construction guarantee constant functioning without blocking as well as precision, easy handling, fast firing action, and simple use.

The tactical version

The Tactical version is equipped as standard with Ghost Ring Sights that are both windage-and elevation-adjustable.

It can also be fitted with an MIL-STD-1913 Picatinny Rail, making it possible to fit all types of targeting device (from optical sights to red dot sights, light intensifiers and thermal chambers) as well as An/Pvs-4 night vision sights.

OPERATION
Benelli Inertia System semiautomatic

GAUGE

CHAMBER

SAFETY ordinary (mechanic and manually operated on trigger) and automatic (against premature firing on disconnecter); large size, reversible (right-/left-handed) safety button

CUT-OFF lever for rapid cartridge replacement and red cocked hammer indicator

TRIGGER LOAD
between 2.500 - 22 AND 28 N and 2.600 Kg (inclusive)

BARREL LENGTH (mm)

MAGAZINE CAPACITY
6 Magnum or 7 standard cartridges (+1 in chamber)

M2 18,5" PISTOL GRIP STOCK	M2 14"+ DOOR-BREACHER PISTOL GRIP STOCK
•	•
12	12
3" MAGNUM	3" MAGNUM
•	•
•	•
•	•
470	355
•	

MAGAZINE CAPACITY
3 Magnum or 4 standard cartridges (+1 in chamber)

STOCK DISTANCE FROM TRIGGER (mm)

SIGHTS
Ghost Ring rear sight with diopter with adjustable windage and elevation and protective side lugs; fixed sight for Ghost Ring Sight

STOCK
Pistol grip fixed drop stock

WEIGHT g (unloaded weapon)

TOTAL LENGTH (mm)

FINISH
black anodised receiver; hammered barrel in Ni-Cr-Mo with blued exterior and chromeplated interior

M2 18,5" PISTOL GRIP STOCK	M2 14"+ DOOR-BREACHER PISTOL GRIP STOCK
	•
360	360
•	•
•	•
3100	3020
1010	901
•	•



Nova has the mag stop system

The mag-stop system, which is an exclusive Benelli patent, means that using an easily accessible button, it is possible to extract the chambered shell without disturbing the ammunition in the magazine. Nova can use all the ammos available on the market.

18,5" MONOBLOCK STOCK/RECEIVER



14"+ DOOR-BREACHER MONOBLOCK STOCK/RECEIVER





The high rubber recoil pad is pressure applied and requires no fastening screws.



A mag-stop button located under the fore-end means that it is possible to extract the chambered cartridge without removing the cartridges in the magazine.



Nova consists of a minimum number of parts, which means that maintenance operations are both quick and simple. The fore-end cap, with its highly ergonomic design, is the only tool required to strip the weapon.

	NOVA 18,5" MONOBLOCK STOCK/RECEIVER	NOVA 14"+ DOOR-BREACHER MONOBLOCK STOCK/RECEIVER
MAG STOP	•	•
GHOST SIGHT 18,5"	•	
GHOST SIGHT 14"		•
TOTAL LENGTH (mm)	1020	910
STOCK DISTANCE FROM TRIGGER (mm)	360	360
WEIGHT (g)	3500	3420

- The shotguns have single action trigger system and 2 kg trigger load.
- The safety is right/left reversible, ordinary (mechanic and manually operated on the trigger) and automatic (against premature firing on disconnecter).
- Finish: hammered barrel in Ni - Cr - Mo; blued exterior and chrome-plated interior.
- Sights: Sight and Ghost Ring Rear Sight; Slug fixed sight and adjustable rear sight.
- Magazine Capacity: 4 standard, 3 magnum, 2 supermagnum (+ 1 in the chamber).

Technopolymer reinforcements

The one-piece stock and receiver is made in sturdy, injection-moulded technopolymer with glass fibre reinforcements. Nova is impervious to humidity, abrasion and shocks, and it can even withstand the effects of solvents and chemical products.

Ghost Sight & Rail

The Tactical version with 18.5" (470 mm) cylindrical barrel is fitted as standard with Ghost Ring Sight and MIL- STD 1913 Picatinny Rail for mounting all types of targeting device and An/Pvs-4 night vision sights.

From 2005 the new pump-action

Conceived and designed in 2005 by the Benelli Armi's Research and development Centre, the SuperNova Pump-Action collection is the most modern product of the entire world panorama of smooth barrel, pump-action shotguns.

18,5" TELESCOPIC STOCK



14"+ DOOR-BREACHER TELESCOPIC STOCK





A mag-stop button located under the fore-end means that it is possible to extract the chambered cartridge without removing the cartridges in the magazine.



Supernova consists of a minimum number of parts, which means that maintenance operations are both quick and simple. The fore-end cap, with its highly ergonomic design, is the only tool required to strip the weapon.

	SUPERNOVA 18,5" TELESCOPIC STOCK	SUPERNOVA 14"+ DOOR-BREACHER TELESCOPIC STOCK
MAG STOP	•	•
GHOST SIGHT 18,5"	•	
GHOST SIGHT 14"		•
TELESCOPIC STOCK	•	•
TOTAL LENGTH (mm)	1020	910
STOCK DISTANCE FROM TRIGGER (mm)	350	350
WEIGHT (g)	3350	3280

- The shotguns have single action trigger system and 2 kg trigger load.
- The safety is right/left reversible, ordinary (mechanic and manually operated on the trigger) and automatic (against premature firing on disconnecter).
- Finish: hammered barrel in Ni - Cr - Mo; blued exterior and chrome-plated interior front and rear.
- Sights: ghost ring sight.
- Magazine Capacity 18,5": 6 standard, 5 magnum or 4 supermagnum (+1 in the chamber).

Telescopic stock

Thanks to extensive technological experience and the precision engineering used to develop it, SuperNova represents the ultimate in the sector.

In the version with Telescopic Stock, it is a powerful shotgun, versatile and resistant however and wherever it is used.

New design details

The new design of this weapon incorporates important and exclusive details in terms of ergonomics. The stock can be quickly adjusted in 5 positions without tools. It can be adjusted from a maximum length of 1020 mm to a minimum of 910 mm, while maintaining all of the shotgun functions, even in the shortened version.





Supernova 14” can also
be fitted with an 18.5”

	SUPERNOVA 14” GRIP HANDLE
MAG STOP	•
14” NO SIGHTS	•
GRIP HANDLE	•
TOTAL LENGTH (mm)	655
STOCK DISTANCE FROM TRIGGER (mm)	350
WEIGHT (g)	2800

barrel and an extension to increase magazine tube capacity (to 5 magnum or 6 standard cartridges +1 in the chamber).

All models have a limited number of parts, which have been assembled in such a way as to allow quick and easy stripping and re-assembly without tools.

- The shotguns have single action trigger system and 2 kg trigger load.
- The safety is right/left reversible, ordinary (mechanic and manually operated on the trigger) and automatic (against premature firing on disconnect).
- Finish: hammered barrel in Ni - Cr - Mo; blued exterior and chrome-plated interior.
- Magazine Capacity: 4 standard, 3 magnum, 2 supermagnum (+ 1 in the chamber).

14” + DOOR-BREACHER GRIP HANDLE



Reliable and resistant

The MR1 semiautomatic rifle is chambered in 5.56 mm (.223 Rem.) and uses the proven A.R.G.O. system developed by Benelli for the M1014.

All steel parts are black phosphated and aluminium parts are hard-anodized in a matt finish.

The MR1 is the first self loading semiautomatic rifle conceived from the ground up for police work; more versatile than a military firearm, it can be adjusted to the physical attributes and the special needs of the single operator.

12,5"+2" TELESCOPIC STOCK





The frame of the MR1

is divided in 2 parts: top receiver and bottom receiver. The bottom receiver is milled from a solid bar stock of aircraft grade light alloy; for maximum strength, the top receiver (permanently affixed to the barrel) is machined from a bar of high quality hardened steel.

Flexible and versatile

Ambidextrous magazine release button and bolt release lever allow the use of MR1 rifle also by left-handed shooters. Manual safety button can be assembled on either side of the firearm.

A quick detachable sling swivel system on front and both sides of the stock make all the combinations of carrying the rifle possible. Large slots on stock and fore-end allow the passage of traditional slings.

	MR1 12,5"+2"
OPERATION Semiautomatic Auto Regulating Gas Operating	•
CALIBER	.223
SAFETY Manual safety catch on trigger guard. Can be inserted with hammer cocked and bolt open or shut inertia firing pin	•
BARREL LENGTH 12,5" (325 mm) + flash-hider	•
MAGAZINE CAPACITY 30 rounds	•
STOCK DISTANCE FROM TRIGGER (mm) with extended stock	352
SIGHTS Post front sight and height and laterally adjustable rear sight	•
WEIGHT g (unloaded weapon) + flash-hider	3150
TOTAL LENGTH (mm) + flash-hider	800 ext. 787 fold.
FINISH black anodised receiver; hammered barrel in Ni-Cr-Mo steel with chrome lining and phosphate-coated exterior	•

Optionals



GHOST RING SIGHT



PICATINNY RAIL



3-RAIL RING



AMMO POUCH



CLEANING KIT



3 POINTS SHOTGUN STRAP



SLING SWIVEL



DOOR-BREACHER AND CHOKE



CASE EXPLORER



G-BAG



PROFESSIONAL DEFENSE

TECHNICAL SPECIFICATION ARE SUBJECT TO CHANGE WITHOUT NOTICE



Learn more about the Benelli Defense world

www.benellidefense.it



CR002410

BENELLI DEFENSE



QUALITY ASSURANCE
SYSTEM CERTIFIED BY THE
ITALIAN MINISTRY OF DEFENCE,
GENERAL DEPARTMENT OF LAND
WEAPONS, ACCORDING TO LAW.
NATO AQAP 2110

Benelli Armi S.p.A.
Via della Stazione, 50 61029
Urbino (PU) - Italy
ph. +39 0722 3071
fax +39 0722 307206

www.benellidefense.it

 **Benelli**